



Wastewater Utility

809 South State Street : Greenfield, Indiana 46140

wwtp@greenfieldin.org

Phone 317-477-4360 Fax 317-477-4361

February 13, 2019

CRANE TRUCK MINIMUM SPECIFICATIONS

The City of Greenfield's Wastewater Utility is requesting quotes for a Chevrolet Silverado MD 4500 with a Knapheide service body and crane. Truck dealers are to contact Matt Ring w/ Kalida Truck Equip., Inc. at 800-686-1617 or mring@kalidatruck.com or other Knapheide dealer to complete the vehicles pricing.

Quotes are to be submitted no later than Feb. 26th at 9:30 am to Lori Elmore, Clerk-Treasurer's Office, 10 South State Street, Greenfield, IN 46140. Write "CRANE TRUCK" on the outside of the envelope and include product brochures and all required documents with your quote. The Clerk Treasurer's fax number is (317) 477-4311 if your time is running short. Call to confirm fax arrival at (317) 477-4310. Be sure to fill out and submit the E-Verify document with your bid. The Board reserves the right to reject or accept any or all bids.

MINIMUM CAB & CHASSIS SPECS

- New 2019 Chevrolet Silverado MD 4500 w/ 4WD, Regular Cab or equal.
- All standard equipment is to be included whether stated in this spec. or not.
- Engine 6.6L Duramax, Turbo-diesel
- Transmission: automatic 6 SPD w/ double over-drive Allison
- Axle limited slip, Dana Spicer Truetrac
- Summit White color w/ Preferred Equipment Group
- Include A Spare Tire, equal to existing front & rear tires
- Seats are to be vinyl, No carpet flooring
- Aluminum Assist Steps
- Recovery hooks, front frame mounted, black
- 165" wheelbase, 84" CA
- Trailer Tow Package
- Audio system w/color display & back-up camera
- Wheels 19.5" X 6.75", Tires 225/70R19.5G
- Warranty 3-year 36,000 miles, plus additional standard warranties

MINIMUM SERVICE BODY SPECIFICATIONS

- 11' Knapheide Service Body, reinforced for crane mounting w/ Through Compartments (Transverse). 50" compartment height, color to be white.

- A 5000 lbs. capacity Venturo, electronic over hydraulic crane with minimum 16' reach shall be mounted on the rear passenger side of the service body. Operating capabilities of up, down, rotate left & right while winch is operating up or down. Equipped with a safety shut down bracket and 2" swivel-safety hook. Control pendant to have a minimum 20' cable and hanger for pendant. Adjustable spot light mounted on bottom side of crane to look into wells. Autocrane cranes are also acceptable.
- Install a police style spot light in passenger side door.
- Install a boom rest with hook restraint. Place a 10" x 10" tread bright aluminum square on each side of the boom restrain to protect the service body from hook scratches and drops.
- 1,500 psi power sprayer with 25' hose, hose auto-reel & wand to be mounted outside of the through compartment in the bed, accessible from passenger side compartment door, a 25 – 50 gallon water storage tank to be mounted on floor of this compartment with drain port through service body.
- A 25-gallon air compressor is to be mounted in the bed near through compartment with a 50'hose and auto-reel.
- Auto-reels are to be mounted on a reinforcing plate on the through compartment.
- Compartment doors are to be sealed with automotive grade gasket material, type 304 stainless steel door hinges & hardware and keyed alike.
- Recessed Exterior LED lighting package to meet Federal Safety Standards
- Interior lighting installed above each compartment to assist in night work.
- Through Compartments to have (2) long shelves, wheel well compartments to have (1) full length shelf on each side and the rear compartments shall have (2) shelves on each side. All shelves shall be adjustable and static.
- Minimum 1/8" steel tread plate floor, plus 3 sides of load space to be protected with full length spray-on bed liner, plus over top of each compartment.
- Install a 120volt / 15amp power converter with plugs accessible in passenger side compartment.
- U.S. Cargo Control "L" Track or equal, aluminum material handling strips mounted on both insides of the bed, approximately 20" above the bed floor. Four (4) Double Stud Fittings with Pear Links are to be supplied for the tie downs.
- 10" automotive style tailgate, inside protected with tread bright aluminum
- 1 - CODE 3 – 21TR, Alternating strobe and/or flashing amber lights facing the front of the vehicle and alternating strobe and/or flashing amber and red lights facing the rear of the vehicle, centrally mounted on top of the truck cab using the ACARI mounting system, lights to be operated by switch in the cab.
- All service body wiring must be ran in protective automotive split loom
- Rear bumpers to be a heavy gauge steel tread-plate bumper w/ 2" ball & pintle hitch, standard 7-pin covered trailer jack, painted gloss black
- Manual –crank outriggers are to be mounted under the rear bumper for crane lifting support
- Vehicles brake, emergency and back-up lighting to be integrally installed in the rear of the service body in shock resistant rubber grommets
- Service body, cab & chassis are to be undercoated
- All standard equipment must be included on the service body unless they have been replaced by a specified item
- Service body, crane, all equipment, shipping, etc. pricing must be forwarded to the truck dealers ASAP so they can complete their bid. Once awarded, body supplier is to make all arrangements to receive and build the complete truck. Delivery is to be made to the Greenfield Wastewater Utility.
- All questions are to be directed to David Scheiter (317) 477-4360.